



Excellence in Infection Control with SFED

SteriMicro™ – Fogger ULV

Ultra-Low Volume Fogger for Air Disinfection.

SteriMicro™ - Fogger ULV is used for fogging all types of water-based disinfectants in closed rooms. **SteriMicro™ - Fogger ULV** breaks the disinfecting liquid into very fine particles (0.1-10 microns), which remain suspended in the air for a long time. This increases the contact time of the disinfectant with micro-organisms in the air. The small particle size also ensures that there is minimum wetting of the surfaces. **SteriMicro™ - Fogger ULV** when used with the right disinfectant ensures proper fogging of closed spaces. **SteriMicro™ - Fogger ULV** is ideally suited for use with water-based disinfectant.



FEATURES SPECIFICATION

- Recommended for use with Disinfectants, biocides, fungicides, etc.
- Highly effective for the critical areas to prevent microbial contamination.
- Generates ultra-fine and non-wetting aerosols.
- No Wet floors and surfaces.
- Uniform spread flow & Ultra low consumption of disinfectant to ensures economy.
- Low maintenance cost and reliable in operation.
- Compatible with all kind of water based Disinfectant Solution.
- High speed Motor drive, maximum reliability, and best performance.
- Nozzle generates aerosol of 0.1-to-10-micron size drops



CE



QMS
INTERNATIONAL



Excellence in Infection Control with SFED

SteriMicro™ – Fogger ULV

Ultra-Low Volume Fogger for Air Disinfection.



AREA OF APPLICATION

- **Aerial disinfection in hospital:** Operation theatres, ICU, clinics.
- **Sterile areas:** Pharmaceutical industry.
- **# Laboratories:** Microbiology, tissue culture.
- **Sanitation treatment:** Foods & Beverage processing plants, dairies, Kitchens.
- **Infection Prevention:** Poultry, hatcheries, animal houses. Veterinary Clinics.
- **Pest control treatment:** Commercial and industrial areas.
- **Deodorizing treatment:** Hotels, food plants.
- **Anti mold sanitizer:** Residential & commercial application.

SPECIFICATION

Voltage	110v/220v
Power	1200W
Capacity	4.5L
Spray distance range in static wind	5-10M
Spraying	0-260 ml per minute
Wire length	5M
For Angel	60 degree up and down adjustable
Dimension	39*27*44cm
Weight	NW 2.8KG/GW3.5KG

SFED India Pvt. Ltd.

ISO 9001: 2015, GMP, CE & ISO 13485: 2016 Compliance Company
 SF-221, 2nd Floor, IT Complex, JMD Megapolis, Sohna Road, Gurgaon, Haryana-122018
 Contact: - 9026326293; Mail - info@sfedindia.in
 www.sfedindia.in